PLUG-IN tower light with rotating mast

The tower light MAXI LIGHT PLUG-IN LED DIALUX is available for diverse rental applications and to supply the users with solid lighting equipment that is easy to transport and meets all site requirements. The additional safety functions ensure that the lamps are protected during transport.

The most flexible and the most powerful lighting solution on the market, allowing the users to connect the tower light to every type of power supply, including an auxiliary supply, a generator and even directly to the network.

FEATURES AND BENEFITS

- Ideal for special event management, projects in urban areas, temporary roads, public construction and lighting.
- Durable, unbreakable LED lamps: more than 20,000 hours.
- Bright coverage area of 3000m² (20 lux on average). - Footboard facilitates dismantling.
- Compact.
- Economic.
- Perforated lamp armatures permitting wind to blow through without causing pressure to the mast.
- The 270° degree mast rotation improves the angle and lighting surface.

		Code	MAXLIGHT230VSW	MAXHYBRIDSW
NEW LAMPS		Model	Maxi-light Plug-in Led	Maxi-light Plug-in & Go Hybrid
LED DIALUX-DUAL		Frequency (Hz)	50/60	50/60
		Rated power hp (kW)	(0,64)	3 (2,2)
		Winch	Manual	Manual
	Ecological	Height (m)	8	8
	No emissions No fuel	Minimum dimension (mm)	1160 × 800 × 2200	1160 × 800 × 2200
		Maxi. dimension developed (mm)	1950 × 1250 × 7200	1950 × 1250 × 7200
		Net weight (kg)	265	296
		Lamp power (W)	160 W × 4	160 W × 4
	Enhanced safety Telescopic vertical mast &	Lamp type	LED	LED
		Lighting area (5 lux min.) (m²)	3000	3000
		Lumen	61000	61000
		Mast rotation	270 °	270 °
		Outlet socket 16 A - 230 V	Yes	Yes
		Trailer	No	No
		Programmable Hour Meter Astro clock/timer	Option	Option
	The other days in the	Grounding cable	Option	Option
LUG-IN LED	Removable foot step	Sound pressure @ 7m (dB)	65	75
		Engine	-	PACLITE*
		Certified	power SAE J 1349	
T.C	Enhanced safety Telescopic			



OPTION

PLUG-IN & GO HYBRID



Removable foot step


*PACLITE ENGINE

Gasoline engine with manual start

Power: 3,1 cv (2,5 kw) Autonomy: 8 h Fuel tank: 101 Sound pressure: 75 (dB)

Code X-TRAIL For serial TX2 connection





Min .1160 × 800 × 2200 (mm)

8m 2900 m²



