

## Submersible flexible shaft pump 72 m<sup>3</sup>/h

Submersible pump for draining and removal of water from trench sand building sites without use of electric power. The FORCE pump can take aggregates as large as 15 mm and offers a more rugged heavy duty design.



norm SAE J1349

## FEATURES AND BENEFITS

- Pump with high output and a capacity of 72 m<sup>3</sup>/h.
- Cast steel impeller.
- Solid size capacity: 15 mm.
- High quality components and strong flexible shaft, 6 m.
- Two-dog coupling identical to FP poker vibrators which enable compatibility and versatility in utilisation between water removal and concreting work.
- Autonomous, portable and lightweight in size, this pump can be used in a multitude of applications.
- Same engine power units used together with FP-37-DC poker vibrators.
- Standard delivery with discharge hose of 10 meters and 3" (75 mm), fireman's quick release coupling.
- 2800 rpm, max. head height 15 m.
- Drive unit with Honda GX160.



POWERED BY  
**HONDA**



Stainless steel impeller



FP  
Couplings compatible with  
PFP-80 pump

### PACK VIB 35 mm + PUMP



### COMPLETE PUMP

PFP80-H	Complete pump 6 m with accessories included + fireman couplings + discharge hose 10 m + Motor Honda GX160
PFP80 Diesel	Complete pump 6 m with accessories included + fireman couplings + discharge hose 10 m + motor HATZ diesel 1B20
PFP80-E 230V	Complete pump 6 m with accessories included + fireman couplings + discharge hose 10 m + motor 230 volt-1-50Hz
104.10.00306	Pack pump set complete + flexible shaft poker FP-37-DC

### PUMP PFP80-H OPTIONS

PFP80P-SH-10M	Fireman coupling mounted to 10 m flat hose
PFP80P-SH-20M	Fireman coupling mounted to 20 m flat hose
PFP80-Pompe	Pump only (shaft + strainer) without accessories
PFP80-PUMP	Strainer only : Pump core
PFP80-OIC	Flexible shaft complete 6 m (inner and exterior part with couplings)
PFP80-FLI	Complete inner flexible shaft 6 m
	Certified power SAE J 1349



Force Pump core

